



PRESCOTT'S, INC.  
OPHTHALMOLOGY

ZEISS OPMI 6FC ON PRESCOTT'S OSM200 FLOOR STAND



WIDE ZOOM  
RANGE 1:6



ADJUSTABLE HAND  
GRIPS WITH  
AUTOCLAVABLE SLEEVES



14 FUNCTION, WATER  
RESISTANT FOOT  
PEDAL



21V 150W HALOGEN  
ILLUMINATION WITH  
SPARE LAMP.

MOTORIZED CONTROL  
UNIT FOR FOCUS, ZOOM,  
XY AND ILLUMINATION  
POWER. 110V/220V  
COMPATIBLE

COMPACT, FLEXIBLE AND ROBUST  
DESIGN, THE OSM200 STAND IS SUITED  
FOR ANY SIZE OFFICE OR OPERATING  
ROOM.

**PRESCOTT'S, INC.**  
*Surgical Microscope Specialists*

## ZEISS OPMI 6FC ON PRESCOTT'S OSM200 FLOOR STAND

<b>MICROSCOPE BODY:</b>	Zeiss OPMI 6FC with integrated beam splitter for co-observation and documentation.
<b>BINOCULARS &amp; EYEPIECES:</b>	Tiltable tube 0-60, f=170 with screw on or push in eyepieces. 10x, 12.5x. Inclined tubes f=125 OR f=170 with screw on or push in eyepieces. 10x, 12.5x. Tiltable tube 0-180, f=170 with screw on or magnetic eyepieces. 10x, 12.5x.
<b>OBJECTIVES:</b>	f=175mm; f=200mm. Focal length corresponds to working distance. Diameter = 48mm.
<b>FOCUSING:</b>	Motorized, 50mm range.
<b>SWIVEL RANGE:</b>	Vertical 360 degrees. Horizontal 330 degrees.
<b>ZOOM SYSTEM:</b>	Motorized, 1:6 magnification range (0.4x to 2.4x factors).
<b>COUPLING:</b>	Geared Angle Coupling, Controlled Manually. Optional motorized XY available.
<b>ILLUMINATION:</b>	Prescott's Mark II 21V 150W Halogen fiber optic illuminator. Spare lamp module. Fiber optic cables: 71" and 87"; Liquid Light Guide 71" and 87".
<b>SUSPENSION SYSTEM:</b>	Prescott's OSM200 floor stand with counterbalanced articulated arm.
<b>CARRYING CAPACITY:</b>	28.6 pounds (13Kg).
<b>SYSTEM HEIGHT:</b>	55 inches (1397mm).
<b>FOOTPRINT:</b>	Base: 23.5 inches (597mm) width X 24 inches (610mm) depth.
<b>OPTIONAL ACCESSORIES:</b>	XY Coupling. +/-25mm coordinate adjustment range with automatic re-center. XY activated by a joystick on the foot control.
<b>OPMI DRAPE:</b>	P/N: DPL 4940-90 (10 qty/Case)
<b>DOCUMENTATION:</b>	Variety of analog and high definition cameras, video adapters, & video capturing available at request.