



PRESCOTT'S, INC.  
OPHTHALMOLOGY

## ZEISS OPMI 6FC ON PRESCOTT'S OSM200 FLOOR STAND



WIDE ZOOM  
RANGE 1:6



ADJUSTABLE HAND  
GRIPS WITH  
AUTOCLAVABLE SLEEVES

COMPACT, FLEXIBLE AND ROBUST  
DESIGN, THE OSM200 STAND IS SUITED  
FOR ANY SIZE OFFICE OR OPERATING  
ROOM.



14 FUNCTION, WATER  
RESISTANT FOOT  
PEDAL



21V 150W HALOGEN  
ILLUMINATION WITH  
SPARE LAMP.

MOTORIZED CONTROL  
UNIT FOR FOCUS, ZOOM,  
XY AND ILLUMINATION  
POWER. 110V/220V  
COMPATIBLE

**PRESCOTT'S, INC.**  
*Surgical Microscope Specialists*

## ZEISS OPMI 6FC ON PRESCOTT'S OSM200 FLOOR STAND

- MICROSCOPE BODY:** Zeiss OPMI 6FC with integrated beam splitter for co-observation and documentation.
- BINOCULARS & EYEPIECES:** Tilttable tube 0-60, f=170 with screw on or push in eyepieces. 10x, 12.5x.  
Inclined tubes f=125 OR f=170 with screw on or push in eyepieces. 10x, 12.5x.  
Tilttable tube 0-180, f=170 with screw on or magnetic eyepieces. 10x, 12.5x.
- OBJECTIVES:** f=175mm; f=200mm. Focal length corresponds to working distance. Diameter = 48mm.
- FOCUSING:** Motorized, 50mm range.
- SWIVEL RANGE:** Vertical 360 degrees. Horizontal 330 degrees.
- ZOOM SYSTEM:** Motorized, 1:6 magnification range (0.4x to 2.4x factors).
- COUPLING:** Geared Angle Coupling, Controlled Manually. Optional motorized XY available.
- ILLUMINATION:** Prescott's Mark II 21V 150W Halogen fiber optic illuminator. Spare lamp module.  
Fiber optic cables: 71" and 87"; Liquid Light Guide 71" and 87".
- SUSPENSION SYSTEM:** Prescott's OSM200 floor stand with counterbalanced articulated arm.
- CARRYING CAPACITY:** 28.6 pounds (13Kg).
- SYSTEM HEIGHT:** 55 inches (1397mm).
- FOOTPRINT:** Base: 23.5 inches (597mm) width X 24 inches (610mm) depth.
- OPTIONAL ACCESSORIES:** XY Coupling. +/-25mm coordinate adjustment range with automatic re-center.  
XY activated by a joystick on the foot control.
- OPMI DRAPE:** P/N: DPL 4940-90 (10 qty/Case)
- DOCUMENTATION:** Variety of analog and high definition cameras, video adapters, & video capturing available at request.